

British Resilient Nrs Gate Valve Grooved Ends




Certificate: UL Listed / FM Approved

Standard: BS EN 1074-2

Connection: Grooved as ISO 6182

Temperature: 0°C to 80°C

W. pressure: PN 16



Specification

Part No.	Part	Standard Specification	Options
1	Valve Body	EN-GJS-450-10	
2	Resilient Wedge Disc	EN-GJS-450-10+EPDM	
3	Stem	Stainless Steel	SS304,SS316
4	Bolt	Carbon Steel Zinc Plated	SS304,SS316
5	Bonnet	EN-GJS-450-10	
6	O-Ring	NBR	EPDM
7	Gland	EN-GJS-450-10	
8	Handwheel	EN-GJS-450-10	Pressed Steel
9	Bolt	SS304	SS316
10	Flat Washer	SS304	SS316
11	Ring Wiper	EPDM	NBR
12	Bolt	SS304	SS316
13	Flat Washer	SS304	SS316
14	O-Ring	NBR	EPDM
15	Washer	Brass HPb59-1	
16	Bonnet Gasket	EPDM	NBR
17	Wedge Nut	Brass HPb59-1	Bronze Z0Sn5-5-5

Note: For special material request other than standard specification, please indicate clearly on the inquiry or order list.

DN		Dimensions (mm)					
Inch	mm	L	H	OD	d	A	B
2"	50	178	218	60.3	57.15	15.88	7.92
2.5"	65	190	230	73.0	69.09	15.88	7.92
2.5"	65	190	230	76.1	72.26	15.88	7.92
3"	80	203	281	88.9	84.94	15.88	7.92
4"	100	229	316	114.3	110.08	15.88	9.52
5"	125	254	393	139.7	135.48	15.88	9.52
5"	125	254	393	141.3	137.03	15.88	9.52
6"	150	267	420	159.0	154.50	15.88	9.52
6"	150	267	420	165.1	160.90	15.88	9.52
6"	150	267	420	168.3	163.96	15.88	9.52
8"	200	292	490	219.1	214.40	19.05	11.13
10"	250	330	626	273.0	268.28	19.05	12.70
12"	300	356	722	323.9	318.29	19.05	12.70

