

British Wafer Butterfly Valve With Tamper Switch



Certificate: UL Listed / FM Approved

Standard: EN 593 / BS 5155


Connection: Flanged as EN 1092-2, etc.

Contact rating: 16A at 125/250VAC; 0.5A at 250VDC; 10A at 36VDC

Temperature: 0° C to 80° C

W. pressure: PN 16

Surface: FBE coating as AWWA C550



Specification

Part No.	Part	Standard Specification	Options
1	Body	EN-GJS-450-10	
2	O-Ring	NBR	EPDM
3	Stub Shaft	SS431	
4	Disc	EN-GJS-450-10+EPDM	EN-GJS-450-10+NBR
5	Hex Nut	Carbon Steel Zinc plated	
6	Signal Gearbox	Body: EN-GJS-450-10	
7	Drive Shaft	SS431	
8	O-Ring	NBR	EPDM
9	End Face Seal	EPDM	NBR

Note: For special material request other than standard specification, please indicate clearly on the inquiry or order list.

DN		Dimensions (mm)										
Inch	mm	A	B	C	L	H1	H	W	ISO5211	ΦE	ΦF	N-ΦM
2"	50	140.5	65	43	122.5	127	202.2	125	F07	70	90	4-Φ10
2.5"	65	153	71	46	122.5	127	202.2	125	F07	70	90	4-Φ10
3"	80	157.5	81	46	122.5	127	202.2	125	F07	70	90	4-Φ10
4"	100	176	95	52	122.5	127	202.2	125	F07	70	90	4-Φ10
5"	125	191	111	56	122.5	127	202.2	125	F07	70	90	4-Φ10
6"	150	202.5	133	56	122.5	139.5	215	225	F07	70	90	4-Φ10
8"	200	243.5	164	60	122.5	198.5	274	225	F10	102	125	4-Φ12
10"	250	273	196	68	122.5	198.5	274	225	F10	102	125	4-Φ12
12"	300	311	226	78	132	198.5	293.5	225	F10	102	125	4-Φ12