


AWWA C502 Dry Barrel Fire Hydrant



- Design Standard: AWWA C502-2014
- Bottom Flange Standard: ASME B16.1
- Working pressure: 300PSI
200PSI and 250PSI available upon request
- Temperature Range: 0°C-100°C



Specification

Part No	Part	Standard Specification	QTY
1	Operating Stem Nut	C95400	1
2	Dirt ShieKd	ASTM A536, 65-45-12	1
3	Stem Lock Nut	C83600	1
4	Upper Barrel	ASTM A536, 65-45-12	1
5	Upper Stem	ASTM 1045	1
6	Stem Breaking Coupling	ASTM A126 CLASS B	1
7	Drain Valve	C83600	1
8	Seat Ring	C83600	1
9	Main Valve	ASTM A283 GRC+EPDM	1
10	Hydrant Cap	ASTM A536, 65-45-12	1
11	Nozzle Cap	ASTM A536, 65-45-12	1
12	Nozzle	C83600	1
13	Lower Barrd	ASTM A536, 65-45-12	1
14	Bottom Plate	ASTM A536, 65-45-12	1
15	Elbow	ASTM A536, 65-45-12	1
16	Breaking Ring	ASTM A126 CLASSB	2
17	Nozzle Cap	ASTM A536, 65-45-12	2

DN	Dimensions (mm)						
Inch	A	B	C	D	E	F	G
4 1/2"	847	461	76	1219	2413	8- φ 22. 2	φ 280