


DOUBLE SCREW BUNDLE-K07、K04



Function: Designed for non-insulated stationary pipe lines in either a horizontal or vertical position.

Material: The main body of the carbon steel, Article rubber EPDM(According to the demand can not use rubber strip)

Finish: Electro-galvanized

Approvals: Underwriters' Laboratories Listed in the U.S. (UL), Canada (CUL), for use with standard steel pipe sizes 1/2" to 12". Factory Mutual Approved for steel pipe sizes 3/4" to 12". Complies with Manufacturers' Standardization Society ANSI/MSS SP-58 (Type 12) which supersedes ANSI/MSS SP-69.

Maximum Temperature: -20°C ~ 110°C

Ordering: Specify size, Finish.

Item	Size	Specification of bolts and Size		A		B	C	D	Max. Rec. Load		
		mm	in	mm	in	mm	mm	mm	Lbs	Kg	N
GSV9	1/2"	M8	5/16"-18UNC	M8/M10	5/16"-18UNC 3/8"-16UNC	8.8	24.5	34.5	299	135	1334
GSV9	3/4"	M8	5/16"-18UNC	M8/M10	5/16"-18UNC 3/8"-16UNC	8.2	27.5	37.5	299	135	1334
GSV9	1"	M8	5/16"-18UNC	M8/M10	5/16"-18UNC 3/8"-16UNC	7.9	31.5	41.5	299	135	1334
GSV9	1-1/4"	M8	5/16"-18UNC	M8/M10	5/16"-18UNC 3/8"-16UNC	8.7	36	46	299	135	1334
GSV9	1-1/2"	M8	5/16"-18UNC	M8/M10	5/16"-18UNC 3/8"-16UNC	8.8	40.5	50.5	299	135	1334
GSV9	2"	M8	5/16"-18UNC	M10/M12	3/8"-16UNC 1/2"-13UNC	8.8	51	71	299	135	1334
GSV9	2-1/2"	M10	3/8"-16UNC	M10/M12	3/8"-16UNC 1/2"-13UNC	15.5	58	78	339	153	1512
GSV9	3"	M10	3/8"-16UNC	M10/M12	3/8"-16UNC 1/2"-13UNC	18.4	66	86	419	189	1868
GSV9	3-1/2"	M10	3/8"-16UNC	M10/M12	3/8"-16UNC 1/2"-13UNC	18.1	70	90	499	225	2224
GSV9	4"	M12	1/2"-13UNC	M10/M12	3/8"-16UNC 1/2"-13UNC	19.7	85	105	599	270	2668
GSV9	5"	M12	1/2"-13UNC	M10/M12	3/8"-16UNC 1/2"-13UNC	20.7	99	119	799	360	3558
GSV9	6"	M12	1/2"-13UNC	M10/M12	3/8"-16UNC 1/2"-13UNC	19.7	112.5	132.5	1059	477	4714
GSV9	8"	M12	1/2"-13UNC	M16	5/8"-11UNC	26.9	135	155	1619	729	7205
GSV9	10"	M12	1/2"-13UNC	M16	5/8"-11UNC	24.8	167	192	2339	1053	10408
GSV9	12"	M12	1/2"-13UNC	M16	5/8"-11UNC	24.7	195.5	220.5	3159	1422	14055