


P-TYPE PIPE BUNDLE-K07、K04



Function: Used to fix pipe directly on channel steel open surface, realizing unidirectional or bidirectional anti-seismic of multi-pipe system.

Material: Carbon steel

Finish: Electro-galvanized, Pre-galvanized

Approvals : FM certification is available from 3/4" to 12"

Maximum Temperature: 343°C (650°F)

Ordering: Specify size, Finish.

Item	Size	Specification of bolts and Size		A	B	C	Max.Rec.Load		
		mm	in	mm	mm	mm	Lbs	Kg	N
GSP9	1/2"	M8	5/16"-18UNC	24.9	25.65	65	299	135	1334
GSP9	3/4"	M8	5/16"-18UNC	30.3	28.35	71	299	135	1334
GSP9	1"	M8	5/16"-18UNC	37	31.7	78.5	299	135	1334
GSP9	1-1/4"	M8	5/16"-18UNC	45.8	36.1	87.5	299	135	1334
GSP9	1-1/2"	M8	5/16"-18UNC	52.8	39.15	94	299	135	1334
GSP9	2"	M8	5/16"-18UNC	64.8	45.15	106.5	299	135	1334
GSP9	2-1/2"	M10	3/8"-16UNC	77.5	51.5	117.5	339	153	1512
GSP9	3"	M10	3/8"-16UNC	93.4	59.45	134	419	189	1868
GSP9	3-1/2"	M10	3/8"-16UNC	106.1	65.8	147	499	225	2224
GSP9	4"	M10	3/8"-16UNC	118.8	72.15	160	599	270	2668
GSP9	5"	M10	3/8"-16UNC	146.7	85.65	190.5	799	360	3558
GSP9	6"	M10	3/8"-16UNC	173.7	99.15	218	1059	477	4714
GSP9	8"	M10	3/8"-16UNC	228.1	124.55	271	1619	729	7205
GSP9	10"	M10	3/8"-16UNC	282	151.5	326	2339	1053	10408
GSP9	12"	M10	3/8"-16UNC	332.9	176.95	377.5	3159	1422	14055