

Style RF-100

unbraided hose with straight nipple



Listings:

Connection: 1"/DN25 x 1/2"/ DN15 or 3/4"/ DN20, NPT Or BSPT

Hose Diameter: O.D.26.8mm/1-1/16" Flow: 22.5mm/7/8"

Maximum service pressure: 14bars/ 203psi

Maximum ambient temperature: 66° C/150° F(UL)



Flexible hose		cULus listing data			
Model	Sprinkler thread size	Max.allow.Sprinkler K-factor	Max.no. of 90°bends	Min.bending radius	EQL of 33.7mm/1" SCH40 Pipe
	DN/in.	Metric/Imprl.	n x 90°	mm /inch	meters/feet
RF-100-700	15 1/2	80/5.6	2	100	8.2/27.0
	20 3/4	202/14.0		3.9	8.5/28.0
RF-100-1000	15 1/2	80/5.6	3	100	11.3/37.0
	20 3/4	202/14.0		3.9	12.5/41.0
RF-100-1200	15 1/2	80/5.6	3	100	14.9/49.0
	20 3/4	202/14.0		3.9	14.3/47.0
RF-100-1500	15 1/2	80/5.6	3	100	19.2/63.0
	20 3/4	202/14.0		3.9	19.5/64.0
RF-100-1800	15 1/2	80/5.6	4	100	23.8/78.0
	20 3/4	202/14.0		3.9	24.4/80.0