


Malleable iron 90° reducing elbow



Certificate: FM Approved / UL Listed

- Size: 1/4"X1/8"-6"X4" (DN8XDN6-DN150XDN100)
- Pressure: class150 / class300
- Dimensions: ANSI B16.3
- Material: Malleable iron ASTM A197
- Threaded: NPT ASME B1.20.1
- Surface: Black / Electrical galvanized / Hot-dip galvanized



Available size (class 150)

SIZE		A (MM)	B(MM)
1/4"X1/8"	DN8XDN6	18.8	19.3
3/8"X1/8"	DN10XDN6	20.5	21.6
3/8"X1/4"	DN10XDN8	22.4	22.9
1/2"X1/4"	DN15XDN8	24.6	24.9
1/2"X3/8"	DN15XDN10	26.4	26.2
3/4"X1/4"	DN20XDN8	26.7	27.4
3/4"X3/8"	DN20XDN10	28.5	28.7
3/4"X1/2"	DN20XDN15	30.5	31
1"X1/4"	DN25XDN8	27	31
1"X3/8"	DN25XDN10	30	32.3
1"X1/2"	DN25XDN15	32	35.5
1"X3/4"	DN25XDN20	34.8	36.8
1-1/4"X3/8"	DN32XDN10	32	36.5
1-1/4"X1/2"	DN32XDN15	34	38.9
1-1/4"X3/4"	DN32XDN20	36.8	41.2
1-1/4"X1"	DN32XDN25	40.1	42.4
1-1/2"X1/2"	DN40XDN15	35	41.5
1-1/2"X3/4"	DN40XDN20	38.6	44.5
1-1/2"X1"	DN40XDN25	41.9	45.7
1-1/2"X1-1/4"	DN40XDN32	46.2	47.8
2"X1/2"	DN50XDN15	37.5	47.5
2"X3/4"	DN50XDN20	40.6	50
2"X1"	DN50XDN25	43.9	51.3
2"X1-1/4"	DN50XDN32	48.3	53.3
2"X1-1/2"	DN50XDN40	51.3	54.9

2-1/2"X3/4"	DN65XDN20	42	57
2-1/2"X1"	DN65XDN25	46	58.7
2-1/2"X1-1/4"	DN65XDN32	50.5	60
2-1/2"X1-1/2"	DN65XDN40	54.9	63.8
2-1/2"X2"	DN65XDN50	60.7	66
3"X3/4"	DN80XDN20	45	65
3"X1"	DN80XDN25	50	67.5
3"X1-1/4"	DN80XDN32	55	70
3"X1-1/2"	DN80XDN40	58	72
3"X2"	DN80XDN50	64	73.4
3"X2-1/2"	DN80XDN65	71.9	75.9
4"X1-1/4"	DN100XDN32	60	85
4"X1-1/2"	DN100XDN40	62	85
4"X2"	DN100XDN50	69	87
4"X3"	DN100XDN80	83.8	91.4
4"X2-1/2"	DN100XDN90	78	90
6"X4"	DN150XDN100	102	125

Available size (class 300)

SIZE		A (MM)	
1/4"	DN8	23.9	
3/8"	DN10	26.9	
1/2"	DN15	31.8	
3/4"	DN20	35.6	
1"	DN25	41.4	
1 1/4"	DN32	49.3	
1 1/2"	DN40	54.1	
2"	DN50	63.5	
2 1/2"	DN65	74.7	
3"	DN80	85.9	
4"	DN100	114	