




Adaptor Flange EN Standard



- Certificate: FM Approved / UL Listed / Vds / LPCB
- Size: 1" - 18" (DN 25 - DN 450)
- Pressure: PN10 / PN16 / PN25
- Dimensions: ANSI B16.3
- Material: ASTM A536, GRADE 65-45-12, QT450-10
- Threaded: ASME B1.20.1, ISO 7-1, GB 7306
- Surface: P: Painted E: Electroplated B: Black S: Epoxy G: Hot-dip Galvanized



Available size

SIZE		OD SIZE	L (MM)	X (MM)	Y (MM)	Z (MM)
1"	DN25	33.7	60.5	115	85	16
1 1/4"	DN32	42.4	60.5	140	100	16
1 1/2"	DN40	48.3	60.5	150	110	16
2"	DN50	57.0	65	165	125	16
2"	DN50	60.3	65	165	125	16
2 1/2"	DN65	76.1	65	185	145	16
3"	DN80	88.9	65	200	160	16
4"	DN100	108.0	70	220	180	16
4"	DN100	114.3	70	220	180	16
5"	DN125	133.0	70	250	210	18
5"	DN125	139.7	70	250	210	18
6"	DN150	159.0	70	285	240	18
6"	DN150	165.1	70	285	240	18
6"	DN150	168.3	70	285	240	18
8"	DN200	219.1	80	340	295	19
10"	DN250	273.0	85	405	355	21
12"	DN300	323.9	90	460	410	24
14"	DN350	355.6	100	520	470	25
16"	DN400	406.4	110	580	525	27
18"	DN450	457.2	115	640	585	20