


Grooved 45° Elbow



- Certificate: FM Approved / UL Listed
- Size: 1" - 24" (DN 25 - DN 600)
- Pressure: 300PSI
- Dimensions: ANSI B16.3
- Material: ASTM A536, GRADE 65-45-12, QT450-10
- Threaded: ASME B1.20.1, ISO 7-1, GB 7306
- Surface: P: Painted E: Electroplated B: Black S: Epoxy G: Hot-dip Galvanized



Available size

SIZE		OD SIZE	L (MM)
1"	DN25	33.7	44
1 1/4"	DN32	42.4	44
1 1/2"	DN40	48.3	44
2"	DN50	60.3	51
2 1/2"	DN65	73.0	57
2 1/2"	DN65	76.1	57
3"	DN80	88.9	64
4"	DN100	108.0	76
4"	DN100	114.3	76
5"	DN125	133.0	83
5"	DN125	139.7	83
5"	DN125	141.3	83
6"	DN150	159.0	89
6"	DN150	165.1	89
6"	DN150	168.3	89
8"	DN200	219.1	108
10"	DN250	267.4	120.5
10"	DN250	273.0	121
12"	DN300	318.5	133
12"	DN300	323.9	133
14"	DN350	355.6	122
14"	DN350	377.0	152
16"	DN400	406.4	184
18"	DN450	457.2	203
20"	DN500	508.0	229
24"	DN600	609.6	280