


# Grooved Cap With Concentric Hole



- Certificate: FM Approved / UL Listed
- Size: 2"×1" - 8"×1" (DN 50×25 - DN 200×25)
- Pressure: 300PSI
- Dimensions: ANSI B16.3
- Material: ASTM A536, GRADE 65-45-12, QT450-10
- Threaded: ASME B1.20.1, ISO 7-1, GB 7306
- Surface: P: Painted E: Electroplated B: Black S: Epoxy G: Hot-dip Galvanized



## Available size

| SIZE          |            | OD SIZE    | L (MM) |
|---------------|------------|------------|--------|
| 2"×1"         | DN50×DN25  | 60.3X33.7  | 23.5   |
| 2 1/2"×1"     | DN65×DN25  | 76.1X33.7  | 24.5   |
| 2 1/2"×1 1/2" | DN65×DN40  | 76.1X48.3  | 23.5   |
| 2 1/2"×2"     | DN65×DN50  | 76.1X60.3  | 24     |
| 3"×1/2"       | DN80×DN15  | 88.9X21.3  | 25.4   |
| 3"×1"         | DN80×DN25  | 88.9X33.7  | 24     |
| 3"×1 1/2"     | DN80×DN40  | 88.9X48.3  | 23.5   |
| 3"×2"         | DN80×DN50  | 88.9X60.3  | 23.5   |
| 4"×1/2"       | DN100×DN15 | 114.3X21.3 | 27     |
| 4"×1"         | DN100×DN25 | 114.3X33.7 | 27     |
| 4"×1 1/2"     | DN100×DN40 | 114.3X48.3 | 25.4   |
| 4"×2"         | DN100×DN50 | 114.3X60.3 | 25.4   |
| 5"×2"         | DN125×DN50 | 139.7X60.3 | 27     |
| 6"×1/2"       | DN150×DN15 | 165.1X21.3 | 27     |
| 6"×1/2"       | DN150×DN15 | 168.3X21.3 | 25.4   |
| 6"×1"         | DN150×DN25 | 159.0X33.7 | 27     |
| 6"×1"         | DN150×DN25 | 165.1X33.7 | 27     |
| 6"×1"         | DN150×DN25 | 168.3X33.7 | 25.4   |
| 6"×2"         | DN150×DN50 | 165.1X60.3 | 27     |
| 6"×1 1/2"     | DN150×DN40 | 168.3X48.3 | 27     |
| 6"×2"         | DN150×DN50 | 168.3X60.3 | 27     |
| 8"×1"         | DN200×DN25 | 219.1X33.7 | 30     |