


Grooved Flange ANSI Standard



- Certificate: FM Approved / UL Listed / VdS / LPCB
- Size: 2" - 24" (DN 50 - DN 600)
- Pressure: CLASS 125 / 150 / 300
- Dimensions: ANSI B16.3
- Material: ASTM A536, GRADE 65-45-12, QT450-10
- Threaded: ASME B1.20.1, ISO 7-1, GB 7306
- Surface: P: Painted E: Electroplated B: Black S: Epoxy G: Hot-dip Galvanized



Available size

SIZE		OD SIZE	A (MM)	B (MM)	C (MM)	D(MM)	E (MM)
2"	DN50	60.3	206	19	152	121	57.5
2 1/2"	DN65	73.0	230	19	178	140	69.8
2 1/2"	DN65	76.1	230	19	178	149	72.7
3"	DN80	88.9	246	19	191	152	85.5
4"	DN100	114.3	280	19	229	191	110.5
5"	DN125	141.3	320	22	254	216	137.4
6"	DN150	168.3	346	24	280	241.3	164.3
8"	DN200	219.1	414.3	30	341.4	298.5	214.9
10"	DN250	273.0	481.2	30.3	405.6	361.95	268.9
12"	DN300	323.9	553.3	30.4	482.6	431.8	318.9
14"	DN350	355.6	590	37	535	476.3	350.6
16"	DN400	406.4	650	37	595	539.8	401.5
18"	DN450	457.2	690	40	635	577.8	452.2
20"	DN500	508.0	765	43	700	635	503
24"	DN600	609.6	875	49	815	749.3	601.6