


Grooved Flange EN Standard



- Certificate: FM Approved / UL Listed / VdS / LPCB
- Size: 1 1/2" - 24" (DN 40 - DN 600)
- Pressure: PN16 / PN25
- Dimensions: ANSI B16.3
- Material: ASTM A536, GRADE 65-45-12, QT450-10
- Threaded: ASME B1.20.1, ISO 7-1, GB 7306
- Surface: P: Painted E: Electroplated B: Black S: Epoxy G: Hot-dip Galvanized



Available size

SIZE		OD SIZE	A (MM)	B (MM)	C (MM)	D(MM)	E (MM)
1 1/2"	DN40	48.3	195	18.5	150	110	45.4
2"	DN50	60.3	220	18.5	165	125	57.5
2 1/2"	DN65	76.1	235	18.5	185	145	72.7
3"	DN80	88.9	255	18.5	195	160	85.5
4"	DN100	108.0	279	18.5	220	180	104.5
4"	DN100	114.3	279	18.5	224	180	110.5
5"	DN125	133.0	312	21.5	250	210	129.2
5"	DN125	139.7	320	23	250	210	135.5
6"	DN150	159.0	346	21.5	280	240	154.8
6"	DN150	165.1	346	21.5	280	240	160.8
6"	DN150	168.3	346	24	280	240	164.3
8"	DN200	219.1	414.3	30	340	295	214.9
10"	DN250	273.0	480	25.5	405	355	268.9
12"	DN300	323.9	530.5	25.5	460	410	318.9
14"	DN350	355.6	580	30	520	470	350.6
16"	DN400	406.4	630	32	580	525	401.5
18"	DN450	457.2	693	36	640	585	452.2
20"	DN500	508.0	770	36	715	650	503
24"	DN600	609.6	895	40	840	770	601.6