



Grooved Reducing Cross With Threaded Branches



- Certificate: FM Approved / UL Listed
- Size: 4"×1" - 6"×3" (DN 100×25 - DN 150×80)
- Pressure: 300PSI
- Dimensions: ANSI B16.3
- Material: ASTM A536, GRADE 65-45-12, QT450-10
- Threaded: ASME B1.20.1, ISO 7-1, GB 7306
- Surface: P: Painted E: Electroplated B: Black S: Epoxy G: Hot-dip Galvanized



Available size

SIZE		OD SIZE	L (MM)
4"×1"	DN100×DN25	114.3X33.7	102
4"×1 1/4"	DN100×DN32	114.3X42.4	102
4"×1 1/2"	DN100×DN40	114.3X48.3	102
4"×2"	DN100×DN50	114.3X60.3	102
4"×2 1/2"	DN100×DN65	114.3X76.1	102
4"×3"	DN100×DN80	114.3X88.9	102
5"×1 1/4"	DN125×DN32	139.7X42.4	124
5"×1 1/2"	DN125×DN40	139.7X48.3	124
5"×2"	DN125×DN50	139.7X60.3	124
5"×2 1/2"	DN125×DN65	139.7X76.1	124
5"×3"	DN125×DN80	139.7X88.9	124
6"×1"	DN150×DN25	165.1X33.7	140
6"×1 1/4"	DN150×DN32	165.1X42.4	140
6"×1 1/2"	DN150×DN40	165.1X48.3	140
6"×2"	DN150×DN50	165.1X60.3	140
6"×2 1/2"	DN150×DN65	165.1X76.1	140
6"×3"	DN150×DN80	165.1X88.9	140