



Grooved Reducing Tee With Threaded Branch



- Certificate: FM Approved / UL Listed
- Size: 2"×1" - 8"×3" (DN 50×25 - DN 200×80)
- Pressure: 300PSI
- Dimensions: ANSI B16.3
- Material: ASTM A536, GRADE 65-45-12, QT450-10
- Threaded: ASME B1.20.1, ISO 7-1, GB 7306
- Surface: P: Painted E: Electroplated B: Black S: Epoxy G: Hot-dip Galvanized



Available size

SIZE		OD SIZE	L (MM)
2"×1"	DN50×DN25	60.3X33.7	70
2"×1 1/4"	DN50×DN32	60.3X42.4	70
2"×1 1/2"	DN50×DN40	60.3X48.3	70
2 1/2"×1 1/4"	DN65×DN32	73.0X42.4	76
2 1/2"×1 1/2"	DN65×DN40	73.0X48.3	76
2 1/2"×2"	DN65×DN50	73.0X60.3	76
2 1/2"×1"	DN65×DN25	76.1X33.7	76
2 1/2"×1 1/2"	DN65×DN40	76.1X48.3	76
2 1/2"×2"	DN65×DN50	76.1X60.3	76
3"×1"	DN80×DN25	88.9X33.7	86
3"×1 1/4"	DN80×DN32	88.9X42.4	86
3"×1 1/2"	DN80×DN40	88.9X48.3	86
3"×2"	DN80×DN50	88.9X60.3	86
3"×2 1/2"	DN80×DN65	88.9X76.1	86
4"×2 1/2"	DN100×DN65	108.0X76.1	102
4"×3"	DN100×DN80	108.0X88.9	102
4"×1"	DN100×DN25	114.3X33.7	102
4"×1 1/4"	DN100×DN32	114.3X42.4	102
4"×1 1/2"	DN100×DN40	114.3X48.3	102
4"×2"	DN100×DN50	114.3X60.3	102
4"×2 1/2"	DN100×DN65	114.3X73.0	102
4"×2 1/2"	DN100×DN65	114.3X76.1	102
4"×3"	DN100×DN80	114.3X88.9	102
5"×1"	DN125×DN25	139.7X33.7	124
5"×1 1/4"	DN125×DN32	139.7X42.4	124
5"×1 1/2"	DN125×DN40	139.7X48.3	124
5"×2"	DN125×DN50	139.7X60.3	124
5"×2 1/2"	DN125×DN65	139.7X76.1	124

5"×3"	DN125×DN80	139.7X88.9	124
6"×2 1/2"	DN150×DN65	159.0X76.1	140
6"×3"	DN150×DN80	159.0X88.9	140
6"×1"	DN150×DN25	165.1X33.7	140
6"×1 1/4"	DN150×DN32	165.1X42.4	140
6"×1 1/2"	DN150×DN40	165.1X48.3	140
6"×2"	DN150×DN50	165.1X60.3	140
6"×2 1/2"	DN150×DN65	165.1X76.1	140
6"×3"	DN150×DN80	165.1X88.9	140
6"×1"	DN150×DN25	168.3X33.7	140
6"×1 1/4"	DN150×DN32	168.3X42.4	140
6"×2"	DN150×DN50	168.3X60.3	140
6"×2 1/2"	DN150×DN65	168.3X73.0	140
6"×3"	DN150×DN80	168.3X88.9	140
8"×2 1/2"	DN200×DN65	219.1X76.1	175
8"×3"	DN200×DN80	219.1X88.9	175