


Malleable iron 90° reducing elbow



- Certificate: FM Approved / UL Listed / BSI / LPCB / NSF 61
- Size: DN15×10 - DN100×80
- Pressure: 2.5 Mpa / PN25
- Dimensions: BS EN10242
- Material: Malleable iron BS EN1562
- Threaded: BSPP (ISO228) / BSPT (ISO7-1)
- Surface: Black / Electrical galvanized / Hot-dip galvanized



Available size

Size	DN	A(mm)	B(mm)	PCS/CTN
1/2"x3/8"	15×10	25	25	270
3/4"x1/2"	20×15	29	30	270
1 "x 3/8"	25×10	29	31	160
1 "x 1/2"	25×15	31	33	160
1 "x 3/4"	25×20	34	35	160
1-1/4"x1/2"	32×10	31	36	100
1-1/4"x1/2"	32×15	34	37	100
1-1/4"x3/4"	32×20	36	40	100
1-1/4"x1"	32×25	40	41	90
1-1/2"x1/2"	40×15	35	41	90
1-1/2"x3/4"	40×20	37	43	90
1-1/2"x1"	40×25	41	45	70
1-1/2"x1-1/4"	40×32	45	47	56
2 "x 1/2"	50×15	37	47	68
2 "x 3/4"	50×20	40	49	52
2"x1"	50×25	43	51	50
2 "x 1-1/4"	50×32	47	53	40
2 "x 1-1/2"	50×40	51	54	30
2-1/2"x1/2"	65×15	40.5	56	46
2-1/2"x3/4"	65×20	43.5	57	40
2-1/2"x1"	65×25	47.5	59	34
2-1/2 "x 1-1/4"	65×32	51.5	61	30
2-1/2 "x1-1/2"	65×40	54.5	61	26
2-1/2"x2"	65×50	59.5	64	24
3 "x1/2"	80×15	42.5	64	36
3 "x 3/4"	80×20	45.5	65	30
3 "x1"	80×25	49.5	67	20
3 "x 1-1/4"	80×32	54.5	69	20
3 "x 1-1/2"	80×40	57.5	71	20

3 "x 2"	80×50	61.5	71	12
3 "x 2-1/2"	80×65	71.5	74	12
4 "x1/2"	100×15	49.5	78	14
4"x3/4"	100×20	53.5	79	14
4 "x1"	100×25	56.5	82	14
4 "x 1-1/4"	100×32	60.5	85	14
4 "x 1-1/2"	100×40	62.5	85	10
4 "x2"	100×50	68.5	86	10
4 "x 2-1/2"	100×65	77.5	89	8
4 "x3"	100×80	82.5	90	8