


Malleable iron Reducing Socket



- Certificate: FM Approved / UL Listed / BSI / LPCB / NSF 61
- Size: DN 8×6- DN 200×150
- Pressure: 2.5 Mpa / PN25
- Dimensions: ASME B16.3, B16.14
- Material: ASTM A197/A197M
- Threaded: ASME B1.20.1
- Surface: Black / Electrical galvanized / Hot-dip galvanized



Available size

SIZE		A (MM)
1/4 "x 1/8"	8×6	25.4
3/8 "x 1/8"	10×6	28.7
3/8 "x 1/4"	10×8	28.7
1/2 "x 1/8"	15×6	31.8
1/2 "x 1/4"	15×8	31.8
1/2 "x 3/8"	15×10	31.8
3/4 "x 1/8"	20×6	36.6
3/4 "x 1/4"	20×8	36.6
3/4 "x 3/8"	20×10	36.6
3/4 "x 1/2"	20×15	36.6
1 "x 1/4"	25×8	42.9
1 "x 3/8"	25×10	42.9
1 "x 1/2"	25×15	42.9
1 "x 3/4"	25×20	42.9
1-1/4"x1/4"	32X8	52.3
1-1/4"x3/8"	32X10	52.3
1-1/4"x1/2"	32×15	52.3
1-1/4"x3/4"	32×20	52.3
1-1/4"x1"	32×25	52.3
1-1/2"x1/4"	40×8	58.7
1-1/2"x3/8"	40×10	58.7
1-1/2"x1/2"	40×15	58.7

1-1/2"x3/4"	40×20	58.7
1-1/2"x1"	40×25	58.7
2 "x1/2"	50×15	71.4
1-1/2"x1-1/4"	40X32	58.7
2 "x3/4"	50×20	71.4
2 "x 1"	50×25	71.4
2 "x1-1/4"	50×32	71.4
2"x1-1/2"	50×40	71.4
2-1/2"x1/2"	65×15	82.6
2-1/2"x3/4"	65×20	82.6
2-1/2"x1"	65×25	82.6
2-1/2"x1-1/4"	65×32	82.6
2-1/2"x 1-1/2"	65×40	82.6
2-1/2"x2"	65×50	82.6
3 "x1/2"	80×15	93.7
3 "x3/4"	80×20	93.7
3 "x 1"	80×25	93.7
3 "x1-1/4"	80×32	93.7
3 "x 1-1/2"	80×40	93.7
3 "x 2"	80×50	93.7
3 "x2-1/2"	80×65	93.7
4 "x 1"	100×25	111.3
4"x 1-1/4"	100×32	111.3
4 "x1-1/2"	100×40	111.3
4 "x 2"	100×50	111.3
4"x2-1/2"	100×65	111.3
4 "x 3"	100×80	111.3
5 "x 4"	125×100	122
6"x 2"	150×50	105
6"x 3"	150×80	105
6"x 4"	150×100	105
8"x6"	200×150	131