


Mechanical Tee With Threaded Branches



- Certificate: FM Approved / UL Listed
- Size: 2"×1" - 8"×4" (DN 50×25 - DN 200×100)
- Pressure: 300 psi
- Dimensions: ANSI B16.3
- Material: ASTM A536, GRADE 65-45-12, QT450-10
- Threaded: ASME B1.20.1, ISO 7-1, GB 7306
- Surface: P: Painted E: Electroplated B: Black S: Epoxy G: Hot-dip Galvanized



Available size

SIZE		OD SIZE	Φ(MM)	L (MM)	K (MM)	H (MM)
2"×1"	DN50×DN25	60.3X33.7	75	116	58	72
2"×1 1/4"	DN50×DN32	60.3X42.4	75	116	63	75
2"×1 1/2"	DN50×DN40	60.3X48.3	75	116	68	75
2 1/2"×1"	DN65×DN25	73.0X33.7	92	128	68	83
2 1/2"×1 1/4"	DN65×DN32	73.0X42.4	92	128	76	72
2 1/2"×1 1/2"	DN65×DN40	73.0X48.3	92	128	76	83
2 1/2"×1"	DN65×DN25	76.1X33.7	92	128	68	83
2 1/2"×1 1/4"	DN65×DN32	76.1X42.4	96	128	76	83
2 1/2"×1 1/2"	DN65×DN40	76.1X48.3	96	128	76	83
3"×1"	DN80×DN25	88.9X33.7	108	151	78	74
3"×1 1/4"	DN80×DN32	88.9X42.4	108	151	78	86
3"×1 1/2"	DN80×DN40	88.9X48.3	108	151	78	86
3"×2"	DN80×DN50	88.9X60.3	108	151	78	101
4"×1"	DN100×DN25	108.0X33.7	130	175	86	76
4"×1 1/4"	DN100×DN32	108.0X42.4	130	175	92	89
4"×1 1/2"	DN100×DN40	108.0X48.3	130	175	92	89
4"×2"	DN100×DN50	108.0X60.3	130	175	96	105
4"×2 1/2"	DN100×DN65	108.0X73.0	130	175	98	110
4"×2 1/2"	DN100×DN65	108.0X76.1	130	175	98	110
4"×3"	DN100×DN80	108.0X88.9	130	175	98	124
4"×1"	DN100×DN25	114.3X33.7	136	183	88	76
4"×1 1/4"	DN100×DN32	114.3X42.4	136	183	94	89
4"×1 1/2"	DN100×DN40	114.3X48.3	136	183	94	89
4"×2"	DN100×DN50	114.3X60.3	136	183	98	105
4"×2 1/2"	DN100×DN65	114.3X73.0	136	183	100	110
4"×2 1/2"	DN100×DN65	114.3X76.1	136	183	100	110
4"×3"	DN100×DN80	114.3X88.9	136	183	100	124
5"×1"	DN125×DN25	133.0X33.7	157	212	100	80

5"×1 1/4"	DN125×DN32	133.0X42.4	158	212	100	93
5"×1 1/2"	DN125×DN40	133.0X48.3	159	212	100	93
5"×2"	DN125×DN50	133.0X60.3	160	212	104	105
5"×2 1/2"	DN125×DN65	133.0X76.1	161	212	104	112
5"×3"	DN125×DN80	133.0X88.9	162	212	107	131
5"×1"	DN125×DN25	139.7X33.7	164	219	103	80
5"×1 1/4"	DN125×DN32	139.7X42.4	164	219	103	93
5"×1 1/2"	DN125×DN40	139.7X48.3	164	219	103	93
5"×2"	DN125×DN50	139.7X60.3	164	219	107	105
5"×2 1/2"	DN125×DN65	139.7X76.1	164	219	107	112
5"×3"	DN125×DN80	139.7X88.9	164	219	110	131
5"×1"	DN125×DN25	141.3X33.7	164	219	103	80
5"×1 1/4"	DN125×DN32	141.3X42.4	164	219	103	93
5"×1 1/2"	DN125×DN40	141.3X48.3	164	219	103	93
5"×2"	DN125×DN50	141.3X60.3	164	219	107	105
5"×2 1/2"	DN125×DN65	141.3X76.1	164	219	107	112
5"×3"	DN125×DN80	141.3X88.9	164	219	110	131
6"×1"	DN150×DN25	159.0X33.7	190	245	116	80
6"×1 1/4"	DN150×DN32	159.0X42.4	190	245	120	90
6"×1 1/2"	DN150×DN40	159.0X48.3	190	245	120	90
6"×2"	DN150×DN50	159.0X60.3	190	245	123	105
6"×2 1/2"	DN150×DN65	159.0X76.1	190	245	123	110
6"×3"	DN150×DN80	159.0X88.9	190	245	123	130
6"×1"	DN150×DN25	165.1X33.7	190	245	116	80
6"×1 1/4"	DN150×DN32	165.1X42.4	190	245	120	90
6"×1 1/2"	DN150×DN40	165.1X48.3	190	245	120	90
6"×2"	DN150×DN50	165.1X60.3	190	245	123	105
6"×2 1/2"	DN150×DN65	165.1X76.1	190	245	123	110
6"×3"	DN150×DN80	165.1X88.9	190	245	123	130
6"×1"	DN150×DN25	168.3X33.7	192	250	117	80
6"×1 1/4"	DN150×DN32	168.3X42.4	192	250	121	90
6"×1 1/2"	DN150×DN40	168.3X48.3	192	250	121	90
6"×2"	DN150×DN50	168.3X60.3	192	250	124	105
6"×2 1/2"	DN150×DN65	168.3X73.0	192	250	124	110
6"×2 1/2"	DN150×DN65	168.3X76.1	192	250	124	110
6"×3"	DN150×DN80	168.3X88.9	192	250	124	130
8"×1"	DN150×DN25	219.1X33.7	240	302	140	80
8"×1 1/4"	DN200×DN32	219.1X42.4	240	302	142	92
8"×1 1/2"	DN200×DN40	219.1X48.3	240	302	142	92
8"×2"	DN200×DN50	219.1X60.3	240	302	150	105
8"×2 1/2"	DN200×DN65	219.1X76.1	240	302	150	115
8"×3"	DN200×DN80	219.1X88.9	240	302	150	134
8"×4"	DN200×DN100	219.1X114.3	246	302	158	167