


Reducing Coupling



- Certificate: FM Approved / UL Listed
- Size: 2 1/2"X2" - 8"X6" (DN 65*50 - DN 200*150)
- Pressure: 300PSI
- Dimensions: ANSI B16.3
- Material: ASTM A536, GRADE 65-45-12, QT450-10
- Threaded: ASME B1.20.1, ISO 7-1, GB 7306
- Surface: P: Painted E: Electroplated B: Black S: Epoxy G: Hot-dip Galvanized



Available size

SIZE		OD SIZE	L (MM)	H (MM)	W (MM)
2 1/2"X2"	DN65XDN50	73X60	143	102	45
2 1/2"X2"	DN65XDN50	76X60	143	102	45
3"X2"	DN80XDN50	89X60	163	118	47
3"X2 1/2"	DN80XDN65	89X73	163	118	47
4"X2"	DN100XDN50	114X60	200	150	50
4"X2 1/2"	DN100XDN65	114X73	200	150	50
4"X2 1/2"	DN100XDN65	114X76	200	150	50
4"X3"	DN100XDN80	114X89	200	150	50
6"X4"	DN150XDN100	165X114	270	200	51
6"X3"	DN150XDN80	168X89	270	200	51
6"X4"	DN150XDN100	168X114	270	200	51
8"X6"	DN200XDN150	219X165	335	260	63
8"X6"	DN200XDN150	219X168	335	260	63